

ZUNANJA ENOTA	MITSUBISHI ELECTRIC POWER INVERTER							
Ogrevanje	do -20°C			do -25°C				
Temp. izhodne vode	60 °c			60 °c				
Hlajenje	do +46 °c			—				
Napajanje, faze/napetost [V]	1/230	1/230	1/230	1/230	3/400	1/230	3/400	3/400
Model zunanje enote	SUZ-SWM40VA	SUZ-SWM60VA	SUZ-SWM80VA	PUD-SWM80VAA	PUD-SWM80YAA	PUD-SWM100VAA	PUD-SWM100YAA	PUD-SWM120YAA
Nominalna grelna moč [kW]	4	6	7,5	8	8	10	10	12
COP (A7/W35)	5,2	4,86	4,7	4,76	4,76	5	5	4,7
SCOP (W35)	4,58	4,61	4,62	4,07	4,45	4,45	4,45	4,43
Varovalke [št.xA]	1x16	1x16	1X16	1x25	3x16	1x30	3x16	3x16
Dim. Plinskih priključkov	1/4", 1/2"	1/4", 1/2"	1/4", 1/2"	1/4", 1/2"	1/4", 1/2"	1/4", 1/2"	1/4", 1/2"	1/4", 1/2"
Maksimalna višinska razlika [m]	30	30	30 5-30 10	30	30	30	30	30
Dolžina plinske povezave [m]	5-30	5-30		2-30	2-30	2-30	2-30	2-30
Prednapolnjenost plina do dolžineplinske povezave [m]	10	10		10	10	10	10	10
Nominalni pretok ogrevalnega medija [l/min]	5-54	5-54	5-54	10-59	10-59	10-59	10-59	10-59
Zvočna moč [dB(A)]	58	60	62	56	56	59	59	60
Teža [kg]	54	54	54	101	114	107	120	120
Dimenzije šxGxV [cm]	84x33x88	84x33x88	84x33x88	105x48x102	105x48x102	105x48x102	105x48x102	105x48x102

