

ZUNANJA ENOTA	MITSUBISHI ELECTRIC ZUBADAN						
Ogrevanje Temp. izhodne vode Hlajenje	do -28°C					do -28°C	do -25°C
	60 °c					60 °c	do +46 °c
Napajanje, faze/napetost [V]	1/230	3/400	3/400	3/400	3/400	3/400	3/400
Model zunanje enote	PUD-SHWM80VAA	PUD-SHWM80YAA	PUD-SHWM100YAA	PUD-SHWM120YAA	PUD-SHWM140YAA	PUHZ SHW140YHA	PUHZ SHW230YKA
Nominalna grelna moč [kW]	8	8	10	12	14	14	23
COP (A7/W35)	5,03	5,03	5,00	4,80	4,70	4,22	3,65
SCOP (W35)	4,53	4,53	4,50	4,48	4,48	4,16	4,18
Varovalke [št.xA]	1x25	3x16	3x16	3x16	3x16	3x16	3x32
Dim. Plinskih priključkov	1/4 , 1/2	1/4 , 1/2	1/4 , 1/2	1/4 , 1/2	1/4 , 1/2	3/8", 5/8"	1/2", 1"
Maksimalna višinska razlika [m]	30	30	30	30	25	30	30
Dolžina plinske povezave [m]	2-30	2-30	2-30	2-30	2-25	2-75	2-80
Prednapolnjenost plina do dolžineplinske povezave [m]	10	10	10	10	10	30	30
Nominalni pretok ogrevalnega medija [l/min]	10-59	10-59	10-59	10-59	10-59	17,9-40,1	28,7-65,9
Zvočna moč [dB(A)]	56	56	59	60	62	70	75
Teža [kg]	102	115	121	120	122	134	148
Dimenzije šxGxV [cm]	105x48x102	105x48x102	105x48x102	105x48x102	105x48x102	95x33x135	105x33x134

